

VPM

- ◆ 105°C 2000 Hours
- ◆ Super Small Diameter 3.55mm or 4mm
- ◆ High Stability, Low ESR, High Frequency
- ◆ RoHS Compliant (2011/65/EU)




■ Specification

Items	Characteristics	
Operation Temperature Range	-55°C~+105°C	
Rated Voltage	6.3~100V	
Capacitance Range	1.2~270μF 120Hz/20°C	
Capacitance Tolerance	±20%(120Hz/20°C)	
Dissipation Factor	Less than standard data 120Hz/20°C	
Leakage Current	Less than standard data charging 2mins with rated voltage, 20°C	
ESR	Less than standard data 100KHz/20°C	
Endurance	After load rated voltage for 2000hours at 105°C, the following specification shall be satisfied after placing capacitor for 16 hours at 20°C	
	Capacitance change	Within±20% of the initial value
	ESR	Not more than 150% of the specified value
	Dissipation Factor	Not more than 150% of the specified value
	Leakage current	Not more than the specified value
Humidity	Store the capacitor at 60°C under the condition of 90%~95%R.H with no load for 1000hrs, the following specifications shall be satisfied after placing capacitor for 16 hours at 20°C.	
	Capacitance change	Within±20% of the initial value
	ESR	Not more than 150% of the specified value
	Dissipation Factor	Not more than 150% of the specified value
	Leakage current	Not more than the specified value

If you have question for leakage current, please apply rated voltage on capacitors at 105°C for 2hours, then test the leakage current again at 20°C.

■ Standard Size



ΦD	B	C	A	H	E	K	α
3.55	3.9	3.9	1.6	0.65±0.10	1.0	0.5MAX	±0.5
4	4.3	4.3	1.8	0.65±0.10	1.0	0.5MAX	

ps: L≥8mm can be mounted horizontally

■ Rated Ripple Current Frequency Correction Factor

Frequency(Hz)	120Hz	1KHz	10KHz	100KHz	300KHz
Correction factor	0.10	0.45	0.50	1.00	1.00

VPM

■ Standard Size

Rated Voltage (Surge Voltage) (V)	Capacitance (μ F)	Size Φ D \times L(mm)	L.C. (μ A,2min)	Tan δ 120Hz	ESR (m Ω 100kHz)	Ripple current (mA/r.m.s) 105°C100kHz
6.3(7.2)	82	3.55 \times 5.8	300	0.12	100	450
6.3(7.2)	120	3.55 \times 7.7	300	0.12	100	650
6.3(7.2)	100	4 \times 5.8	300	0.12	100	650
6.3(7.2)	150	4 \times 7.7	300	0.12	100	850
6.3(7.2)	220	3.55 \times 11	300	0.12	60	950
6.3(7.2)	270	4 \times 11	415	0.12	60	1250
10(11.5)	47	3.55 \times 5.8	300	0.12	100	450
10(11.5)	68	3.55 \times 7.7	300	0.12	100	650
10(11.5)	68	4 \times 5.8	300	0.12	100	650
10(11.5)	100	4 \times 7.7	300	0.12	100	850
10(11.5)	120	3.55 \times 11	300	0.12	60	950
10(11.5)	180	4 \times 11	440	0.12	60	1250
16(18.4)	27	3.55 \times 5.8	300	0.12	100	450
16(18.4)	39	3.55 \times 7.7	300	0.12	100	650
16(18.4)	39	4 \times 5.8	300	0.12	100	650
16(18.4)	56	4 \times 7.7	300	0.12	100	850
16(18.4)	68	3.55 \times 11	300	0.12	60	950
16(18.4)	100	4 \times 11	384	0.12	60	1250
25(28.8)	15	3.55 \times 5.8	300	0.12	100	350
25(28.8)	22	3.55 \times 7.7	300	0.12	100	500
25(28.8)	22	4 \times 5.8	300	0.12	100	500
25(28.8)	33	4 \times 7.7	300	0.12	100	650
25(28.8)	47	3.55 \times 11	300	0.12	100	750
25(28.8)	68	4 \times 11	340	0.12	100	950
35(41)	12	3.55 \times 5.8	300	0.12	100	350
35(41)	18	3.55 \times 7.7	300	0.12	100	500
35(41)	18	4 \times 5.8	300	0.12	100	500
35(41)	22	4 \times 7.7	300	0.12	100	650
35(41)	33	3.55 \times 11	300	0.12	100	750
35(41)	56	4 \times 11	329	0.12	100	950
50(58)	4.7	3.55 \times 5.8	300	0.12	100	350
50(58)	6.8	3.55 \times 7.7	300	0.12	100	500
50(58)	6.8	4 \times 5.8	300	0.12	100	500
50(58)	12	3.55 \times 11	300	0.12	100	750
50(58)	10	4 \times 7.7	300	0.12	100	650
50(58)	22	4 \times 11	300	0.12	100	950
63(73)	3.9	3.55 \times 5.8	300	0.12	100	350
63(73)	5.6	3.55 \times 7.7	300	0.12	100	500
63(73)	5.6	4 \times 5.8	300	0.12	100	500
63(73)	8.2	4 \times 7.7	300	0.12	100	650
63(73)	10	3.55 \times 11	300	0.12	100	750
63(73)	15	4 \times 11	300	0.12	100	950
80(92)	2.2	3.55 \times 5.8	300	0.12	100	350

VPM

■ Standard Size

Rated Voltage (Surge Voltage) (V)	Capacitance (μ F)	Size Φ D \times L(mm)	L.C. (μ A,2min)	Tan δ 120Hz	ESR (m Ω 100kHz)	Ripple current (mA/r.m.s) 105°C100kHz
80(92)	3.3	3.55 \times 7.7	300	0.12	100	500
80(92)	2.7	4 \times 5.8	300	0.12	100	500
80(92)	4.7	4 \times 7.7	300	0.12	100	650
80(92)	5.6	3.55 \times 11	300	0.12	100	750
80(92)	8.2	4 \times 11	300	0.12	100	950
100(115)	1.2	3.55 \times 5.8	300	0.12	100	350
100(115)	1.8	3.55 \times 7.7	300	0.12	100	500
100(115)	1.8	4 \times 5.8	300	0.12	100	500
100(115)	2.2	4 \times 7.7	300	0.12	100	650
100(115)	3.3	3.55 \times 11	300	0.12	100	750
100(115)	4.7	4 \times 11	300	0.12	100	950