



1 2 3		4 5 6			7		8 9		10 11 12			13 14 15 16				17	
系列	代码	额定容量(μF)	代码	容量范围	代码	额定电压(V)	代码	尺寸(mm)	代码	ESR(mΩ)	代码	额定温度(°C)	代码				
TPB14	TPB	1	1R0	±20%	M	16	1C	3.5*2.8*1.4	B14	9	009R	85	D				
TPB19	TPB	1.5	1R5			20	1D	3.5*2.8*1.9	B19	11	011R	105	N				
TPB26	TPB	2.2	2R2			25	1E	3.5*2.8*2.6	B26	15	015R	125	H				
TQB19	TQB	2.7	2R7			35	1V	7.3*4.3*1.5	D15	20	020R						
TQD15	TQD	3.3	3R3			50	1H	7.3*4.3*1.9	D19	21	021R						
TQD19	TQD	3.9	3R9			63	1J	7.3*4.3*2.8	D28	35	035R						
TQD28	TQD	4.7	4R7			75	1K	7.3*4.3*4.0	D40	45	045R						
TQD42	TQD	5.6	5R6			100	1L	7.3*4.3*4.2	D42	70	070R						
TQW19	TQW	6.8	6R8					7.3*6.0*1.9	W19	80	080R						
TQW42	TQW	8.2	8R2					7.3*6.0*4.2	W42	90	090R						
		10	100							100	100R						
		12	120							150	150R						
		15	150							200	200R						
		22	220							300	300R						
		27	270														
		33	330														
		39	390														
		47	470														
		56	560														
		68	680														
		82	820														
		100	101														
		120	121														
		150	151														
		180	181														
		220	221														
		270	271														
		330	331														
		390	391														
		470	471														
		560	561														
		680	681														
		820	821														
		1000	102														
		1200	122														
		1500	152														

代码规则：前两位数加上后面零的个数，R代表小数点